

GETAC



GETAC recommends Windows Vista® Business

Secure Access and Keep Your Data Safe!

Rugged Notebook

- Designed to meet MIL-STD 810F
- Trusted Platform Module 1.2, Fingerprint Scanner and Smart Card Support
- Shock Mounted Hard Drive
- Vibration & Drop-shock Resistant
- Water Resistant Design
- Integrated Handle
- Sunlight Readable Display
- Magnesium Alloy Case
- Versatile Wireless Access: WLAN, WWAN and Bluetooth
- Media-Bay Features Maximizes Flexibility and Customized Applications

Rugged Mobile Computing Solutions
BUILT TO SURVIVE

P470 Rugged Notebook

SPECIFICATIONS

Ruggedness	MIL-STD 810F Vibration, temperature, Humidity, and Shock compliance Magnesium alloy case I/O port doors Shock-mounted removable HDD Drop-shock resistant
CPU	Intel® Core™ 2 Duo T7200 2.0GHz processor 667 MHz FSB 4MB L2 cache
Memory	1GB DDR2 expandable to 2GB
VGA Controller	Integrated in Intel® 945GM, 128MB shared memory
Display	14.1" WXGA (1280 x 800) TFT LCD Optional touch screen Optional sunlight readable display
Storage	SATA 120GB expandable to 160GB
Media Bay	DVD Combo Optional DVD Dual Optional 2nd battery Optional 2nd HDD 80/120 GB Design reserve for customized I/O port
Webcam	1.3M pixels camera
Expansion Slot	PCMCIA Type II x 1
Smart Card reader	Smart card reader x 1
Express Card	Express card 34/54mm x 1
Memory Card Reader	MS / MS PRO / SD / MMC card reader
Communication Interface	10/100/1000 base-T Ethernet 56K ITU V.92 modem Intel® PRO/Wireless 3945 a/b/g Optional GPS (with internal antenna) Bluetooth(V2.0+EDR class 2) Optional EV-DO/GSM/GPRS/EDGE/UMTS/WCDMA/HSDPA
Security	Optional fingerprint scanner TPM 1.2 Kensington lock
Power	AC adapter (90W, 100-240V, 50/60Hz) Li-Ion smart battery (4700mAh ~ 5200mAh) Optional Li-Ion smart battery (7200mAh) Optional Media Bay battery pack (3600mAh)
Dimensions & Weight	333 x 254~295 x 42 mm (13.1" x 10"~11.6" x 1.65"), 2.95kg (6.4lb)
Operating System	Genuine Windows® XP Professional
Environmental Spec	Operating Temp: 0°C to 45°C / 32°F to 113°F (Optional low temperature: -15°C / 5°F) Storage Temp: -40°C to 70°C / -40°F to 158°F Humidity: 5% to 95% RH, non-condensing

*Specifications subject to change without notice.

GETAC recommends Windows Vista® Business



Backside

4800 mAh Li-Ion primary battery pack
External VGA x 1
Serial Port x 1



Leftside

ExpressCard x 1	PCMCIA Type II x 1
1394a x 1	USB 2.0 x 1
4 in 1 Card Reader x 1	RJ-45 x 1
RJ-11 x 1	Headphone OUT x 1
Microphone x 1	DC IN x 1



Rightside

USB 2.0 x 2
Media Bay x 1
Smart Card Reader x 1
Shock-mount Hard Drive x 1

ACCESSORIES

Vehicle dock
Port replicator
Carrying bag
Shoulder strap

GETAC US
20762 Linear Lane,
Lake Forest, CA 92630, USA
TEL: +1-949-699-2888
Toll Free: +1-866-GO-GETAC
(1-866-464-3822)
<http://www.getac.com>

GETAC EUROPE
Nedge Hill
Telford TF3 3AH, UK
TEL: +44 1952 207 231

GETAC GLOBAL
9F, No. 75,
Ming-Sheng East Rd., Sec. 3,
Taipei, Taiwan, R.O.C.
TEL: +886-2-2501-8231

SALES CONTACT

- **North America:**
Ruggedsales@getac.com
- **South America:**
SouthAmericasales@getac.com
- **EMEA:**
EMEAsales@getac.com
- **APEC:**
APECsales@getac.com
- **OEM/ODM:**
ODM.sales@getac.com

SERVICE CONTACT

- Global Service:
Support@getac.com
- US Toll Free:
+1-866-EZGETAC
(1-866-394-3822)

MARKETING CONTACT

- Global Marketing
Globalmarketing@getac.com
- US Marketing
USmarketing@getac.com