

GETAC



Small Rugged | Rugged | **Fully Rugged** | Ultra Rugged



GETAC recommends Windows
Vista® Business

Work Anyway You Like!

Convertible Tablet

- Assorted Display Convertible for Laptop and Tablet
- 10.4" Screen or 12.1" Wide Screen
- Designed to Meet MIL-STD 810F and IP54
- Full Magnesium Alloy Case with Hand Strap
- Shock-mounted Removable HDD
- Sunlight Readable Display Solution Up to 1200 Nits with Touch Screen for 10.4"
- Integrated GPS and Wireless Access Capable
- Waterproof Reversible Camera



Rugged Mobile Computing Solutions

BUILT TO SURVIVE

www.getac.com

V100

V100 Convertible Tablet

SPECIFICATIONS

Ruggedness	Fully rugged MIL-STD 810F and IP54 compliance Full magnesium alloy case Sealed ports and connectors Shock-mounted removable HDD Vibration & drop-shock resistant
CPU	Intel® Core™ 2 Duo Merom U7600 1.2GHz processor 533 MHz FSB 2MB L2 cache
Memory	1GB DDR2 expandable to 2GB
VGA Controller	Integrated in Intel® 945GMS Default 128MB shared memory
Display	10.4" XGA(Optional 12.1"WXGA) TFT LCD Touch screen or optional digitizer Optional sunlight readable display Optional 1200 nits SR display with touch screen on 10.4"
Storage	SATA 120GB expandable to 250GB
Keyboard	Waterproof membrane keyboard Optional waterproof or LED back-lit rubber keyboard
Webcam	Integrated 200 degree reversible 1.3M pixels camera
Pointing Device	Pressure sensitive touch screen (optional digitizer) Glide touchpad with scroll bar
Expansion Slot	PCMCIA Type II x 2 or Type III x 1
Smart Card reader	Optional smart card reader(occupies one PCMCIA type-II slot)
Memory Card Reader	SD card reader
Communication Interface	10/100/1000 base-T Ethernet 56K ITU V.92 modem Intel® PRO/Wireless 3945 a/b/g Optional GPS (choose either GPS or webcam) Bluetooth(V2.0+EDR class 2) Optional EV-DO/GSM/GPRS/EDGE/UMTS/WCDMA/HSDPA
Security	TPM 1.2 Kensington lock
Power	AC adapter (90W, 100-240V, 50/60Hz) Li-Ion smart battery (5200mAh) Optional Li-Ion smart battery (7800mAh)
Dimensions & Weight	10.4" : 285 x 222 x 49 mm (11.2" x 8.7" x 1.9"), 2.2kg (4.9lbs) 12.1"W : 311 x 222 x 49 mm (13" x 8.7" x 1.9"), 2.45kg (5.4lbs)
Operating System	Genuine Windows Vista® Business Genuine Windows® XP Professional Genuine Windows® XP Tablet PC Edition 2005
Environmental Spec	Operating Temp: 0°C to 55°C / 32°F to 131°F (Optional low temperature -20°C / -4°F) Storage Temp: -40°C to 70°C / -40°F to 158°F Humidity: 5% to 95% RH, non-condensing

*Specifications subject to change without notice.

GETAC recommends Windows
Vista® Business



Backside

Line out	x 1	Microphone	x 1
(Default) VGA	x 1	RS232	x 1
(Option 1) RS232	x 1	RS422	x 1
(Option 2)		RS232	x 2



Leftside

DC In	x 1	USB 2.0	x 2
RJ-11	x 1	RJ-45	x 1
PCMCIA	x 2	SD card reader	x 1



Rightside

Battery	x 1	HDD	x 1
---------	-----	-----	-----

ACCESSORIES

Vehicle dock
Battery charger
Vehicle adapter (90Watts, 12-32V)
Carrying bag
External DVD Multi
Digitizer stylus
Touch screen stylus

GETAC US
20762 Linear Lane,
Lake Forest, CA 92630, USA
TEL: +1-949-699-2888
Toll Free: +1-866-520-GETAC
(1-866-464-3822)
<http://www.getac.com>

GETAC EUROPE
Nedge Hill
Telford TF3 3AH, UK
TEL: +44 1952 207 231

GETAC GLOBAL
9F, No. 75,
Ming-Sheng East Rd., Sec. 3,
Taipei, Taiwan, R.O.C.
TEL: +886-2-2501-8231

SALES CONTACT

- North America:
RuggedSales@getac.com
- South America:
SouthAmericasales@getac.com
- EMEA:
EMEAsales@getac.com
- APEC:
APECsales@getac.com
- OEM/ODM:
ODM_sales@getac.com

SERVICE CONTACT

- Global Service:
Support@getac.com
- US Toll Free:
+1-866-EGOTAC
(1-866-394-3822)

MARKETING CONTACT

- Global Marketing
GlobalMarketing@getac.com
- US Marketing
USMarketing@getac.com